

GUANTE JUBA - DM34402L JUBA

Guante sin costuras de 100% Nylon® peso ligero color blanco



NORMATIVA



ESPECIALES

GUANTES DE TRABAJO RECOMENDADOS PARA:

- Inspección de calidad.
- Limpieza y servicios públicos.
- Operaciones mecánicas ligeras.
- Manejo de piezas pequeñas.
- Proceso de acabado de industria, automoción y electrodomésticos.

CARACTERÍSTICAS

- No desprende pelusa.
- Tecnología 'pre-steam', que permite que el guante mantenga su forma original después de lavado.
- Amplio tallaje.
- Óptimo ajuste a la mano.
- Color gris para ambientes más sucios (DM3440GYMW).
- Peso medio (DM3440MW)

Nylon®

código	acabado	color	grueso	largo	talla	embalaje
DM3-440-2L	Liso	Blanco		S -		
				23cm		
			Galga 13	M -	S/7	12
				24cm	M/8	pares/paquete
			Peso ligero	L -	L/9	240
				25cm	XL/10	pares/caja
				XL -		

26 cm

MÁS INFORMACIÓN

Color	Grueso	Largo	Tallas	Embalaje	
	Blanco	Galga 13	S - 23 cm M - 24 cm L - 25 cm XL - 26 cm	7/S 8/M 9/L 10/XL	12 pares/paquete 240 pares/caja

NORMATIVAS


EN388:2016



EN388:2016 Protective gloves against mechanical risks.

The EN388: 2003 standard is renamed EN388: 2016, the year of its revision. The reason for the modification is given by the discrepancies in the results between laboratories in the knife cut test, COUP TEST. Materials with high levels of cut produce a dulling effect on the circular blades, which undermines the result.

The new regulation was published in November 2016 and the previous one is from the year 2003. During these 13 years, there has been a great innovation in the materials for the manufacture of cutting gloves, they have forced to introduce changes in the tests to be able to measure with more rigorous levels of protection. If you want to know more about the main changes in these regulations, you can consult it through our website www.jubappe.es



- A - Abrasion resistance (X, 0, 1, 2, 3, 4)
- B - Blade Cut Resistance (X, 0, 1, 2, 3, 4, 5)
- C - Tear resistance (X, 0, 1, 2, 3, 4)
- D - Puncture resistance (X, 0, 1, 2, 3, 4)
- E - Cutting by sharp objects ISO 13997 (A, B, C, D, E, F)
- F - Impact test complies / does not comply (It is optional. If it complies, put P)

En388:2016 performance levels	1	2	3	4	5
6.1 abrasion resistance (cycles)	100	500	2000	8000	-
6.2 blade cut resistance (index)	1,2	2,5	5	10	20
6.4 tear resistance (newtons)	10	25	50	75	-
6.5 puncture resistance (newtons)	20	60	100	150	-

Eniso13997:1999 performance levels	A	B	C	D	E	F
6.3 tdm: cut resistance (newtons)	2	5	10	15	22	30