

PU GLOVES JUBA - KSCP300 KEY SAFETY

HPPE / Polyester / spandex shell with PU palm coating



NORMATIVE



EN 388:2016+A1:2018



4X42B



WORKING GLOVES SUITABLE FOR:

- Automotive industry
- Plastic injection and molding.
- Glass industry.
- Aeronautics and renewables.
- Home appliance industry.

CHARACTERISTICS

- Excellent performance against wear and tear and superficial cuts.
- Precise grip In dry, slightly moist or greasy conditions.
- Fresh feeling thanks to its breathability.
- Available with individual header card for retail (HKSCP300).

MATERIALS	COLOUR	THICKNESS	LENGTH	SIZES	PACKAGING
Polyurethane	Grey	Gauge 13	XS - 22 cm S - 23 cm M - 24 cm L - 25 cm XL - 26 cm XXL - 27 cm	6/XS 7/S 8/M 9/L 10/XL 11/XXL	12 pairs/package 120 pairs/box

NORMATIVES


EN 388:2016+A1:2018



EN388:2016 Protective gloves against mechanical risks.

The EN388: 2003 standard is renamed EN388: 2016, the year of its revision. The reason for the modification is given by the discrepancies in the results between laboratories in the knife cut test, COUP TEST. Materials with high levels of cut produce a dulling effect on the circular blades, which undermines the result.

The new regulation was published in November 2016 and the previous one is from the year 2003. During these 13 years, there has been a great innovation in the materials for the manufacture of cutting gloves, they have forced to introduce changes in the tests to be able to measure with more rigorous levels of protection.



- A - Abrasion resistance (X, 0, 1, 2, 3, 4)
- B - Blade Cut Resistance (X, 0, 1, 2, 3, 4, 5)
- C - Tear resistance (X, 0, 1, 2, 3, 4)
- D - Puncture resistance (X, 0, 1, 2, 3, 4)
- E - Cutting by sharp objects ISO 13997 (A, B, C, D, E, F)
- F - Impact test complies / does not comply (It is optional. If it complies, put P)

En388:2016 performance levels

	1	2	3	4	5
6.1 abrasion resistance (cycles)	100	500	2000	8000	-
6.2 blade cut resistance (index)	1,2	2,5	5	10	20
6.4 tear resistance (newtons)	10	25	50	75	-
6.5 puncture resistance (newtons)	20	60	100	150	-

Eniso13997:1999 performance levels

	A	B	C	D	E	F
6.3 tdm: cut resistance (newtons)	2	5	10	15	22	30